

# Eaton FWP-40B

Catalog Number: FWP-40B

Eaton Bussmann series FWP high speed fuse, 250 Vac/dc, 40A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud



Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed cylindrical fuse	FWP-40B
	UPC
	051712795982
<b>EAN</b>	<b>Product Length/Depth</b>
5027590500753	102 mm
<b>Product Height</b>	<b>Product Width</b>
21 mm	21 mm
<b>Product Weight</b>	<b>Warranty</b>
93.6 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	UL Recognized
	CSA Certified

## defaultTaxonomyAttributeLabel

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

40 A

### Breaking capacity

200 kA

### Fuse indicator

Non Indicating

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC/DC

### Fuse size

22 x 58 mm

### Rated switching capacity

200 A

### Rated voltage AC

700 V

### Rated voltage DC

700 V

### Mounting dimension

M8

### Center-to-center distance of connections

89.7 mm

### Current type

AC/DC

### Class

Class aR

### Clearing (I2T)

320 at 700 V

## Resources

### Catalogs

Bussmann series complete full line catalog no. 1007

Watt losses

12 W

Fuse shape

Center bolted tags

Pre arc (I2T)

76

Color

None

Interrupt rating

200 kAIC Vac

50 kAIC at 700 Vdc

50 kAIC at 300 Vdc

200 kAIC at 300 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

700 Vac, 700 Vdc (UL)

Fuse type

FWP-B

Fuse system (according to IEC 60269)

Other