

# Eaton FWP-5AS14FI

Catalog Number: FWP-5AS14FI

Fuse-link, high speed, 5 A, AC 700 V, 14 x 51 mm, aR, UL, with striker



Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed cylindrical fuse	FWP-5AS14FI
	<b>EAN</b>
	5027590500975
<b>Product Length/Depth</b>	<b>Product Height</b>
52 mm	15 mm
<b>Product Width</b>	<b>Product Weight</b>
15 mm	21.2 g
<b>Compliances</b>	<b>Certifications</b>
CE	UL 248-13
RoHS Compliant	
EAC	

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

5 A

### Breaking capacity

200 kA

### Frequency rating - max

62 Hz

### Frequency rating - min

45 Hz

### Fuse indicator

Top fuse status indicator

### Release characteristic

Other

### Utilization category

gR (general purpose semiconductor protection)

### Voltage type

AC

### Fuse size

22 x 58 mm

### Clearing (I<sup>2</sup>T)

11

### Watt losses

1.5 W

### Fuse shape

Cylindrical

### Pre arc (I<sup>2</sup>T)

2

### Interrupt rating

200 kAIC

### Fitted with:

Striker

## Resources

### Catalogs

[IEC high speed fuse links](#)

### Technical data sheets

[720025 FWP](#)

Construction size

14 mm x 51 mm

Material

Ceramic

Voltage rating

690 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)