

Eaton FWP-5B

Catalog Number: FWP-5B

Eaton Bussmann series FWP high speed fuse, 250 Vac/dc, 5A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-5B
	UPC
	051712557849
EAN	Product Length/Depth
5027590500982	60 mm
Product Height	Product Width
40 mm	86 mm
Product Weight	Warranty
25.4 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

5 A

Breaking capacity

50 kA

Fuse indicator

Non Indicating

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Rated switching capacity

50 A

Rated voltage AC

700 V

Rated voltage DC

700 V

Mounting dimension

M6

Center-to-center distance of connections

63.35 mm

Current type

AC/DC

Class

Class aR

Clearing (I2T)

10 at 700 V

Watt losses

1.5 W

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Technical data sheets

[FWP NA bolted fuse-links](#)

Fuse shape

Cylindrical, center bolted tags

Pre arc (I2T)

1.6

Color

None

Interrupt rating

50 kAIC at 700 Vdc

200 kAIC Vac

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

700 Vac, 700 Vdc (UL)

Fuse type

FWP-B

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia