Eaton FWP-63A22F

Catalog Number: FWP-63A22F

Eaton Bussmann series FWP high speed fuse, 700 Vac, 700 Vdc (UL), 63A, 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse

EAN

5027590501019

Product Height 23 mm

Product Weight 62.6 g

Compliances CE Marked RoHS Compliant FWP-63A22F

Catalog Number

051712796576

Product Length/Depth 58 mm

Product Width 23 mm

Warranty Not Applicable

Certifications UL Recognized CSA Certified





defaultTaxonomyAttributeLabel

Туре

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

63 A

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Non Indicating

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

22 x 58 mm

Class

Class aR

Clearing (I2T)

4000

Watt losses

15 W

Fuse shape

Cylindrical

Minimum melting

280 I2t (A2 sec)

Pre arc (I2T)

280

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Used with

Finger safe holders/blocks and striker

Color

White

Interrupt rating

200 kAIC

Connection

Ferrule end x ferrule end

Construction size

22 mm x 58 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating 700 V

Fuse type

FWP-A22F



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia