

Eaton FWP-80B

Catalog Number: FWP-80B

UL 1077 Industrial Miniature Circuit Breaker - Supplementary Protector, 16A, 10-20X /n trip, Single-pole, Standard terminals

General specifications



Photo is representative

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-80B
	UPC
	051712796026
EAN	Product Length/Depth
5027590501132	112 mm
Product Height	Product Width
25 mm	25 mm
Product Weight	Warranty
108 g	Not Applicable
Compliances	Certifications
CE Marked	CSA Certified
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

80 A

Breaking capacity

200 kA

Fuse indicator

Non Indicating

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

22 x 58 mm

Rated switching capacity

200 A

Rated voltage AC

700 V

Rated voltage DC

700 V

Mounting dimension

M8

Center-to-center distance of connections

91.5 mm

Current type

AC/DC

Class

Class aR

Clearing (I2T)

2400 at 700 V

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Technical data sheets

[FWP NA bolted fuse-links](#)

Watt losses

21 W

Fuse shape

Center bolted tags

Pre arc (I2T)

360

Color

None

Interrupt rating

200 kAIC Vac

50 kAIC at 700 Vdc

50 kAIC at 300 Vdc

200 kAIC at 300 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

700 Vac, 700 Vdc (UL)

Fuse type

FWP-B

Fuse system (according to IEC 60269)

Other