

Eaton FWS-15A20F

Catalog Number: FWS-15A20F

Eaton Bussmann series high speed traction fuse, 15A, 50 kAIC, Fuse, Class gS



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed traction fuse	FWS-15A20F
	UPC
	051712570695
EAN	Product Length/Depth
5027590501248	127 mm
Product Height	Product Width
20 mm	20 mm
Product Weight	Warranty
96.9 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated

defaultTaxonomyAttributeLabel

Type

Fuse

Application

traction

Amperage Rating

15 A

Breaking capacity

50 kA

With striker

No

Voltage type

AC/DC

Utilization category

gL/gG (cable protection/equipment protection)

Release characteristic

Other

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Fuse size

20 x 127 mm

Class

Class gG

Clearing (I2T)

209 at 750 Vdc

Watt losses

5 W

Fuse shape

Cylindrical

Pre arc (I2T)

209

Mounting dimension

Other

Current type

Resources

Catalogs

[Traction fuse-links](#)

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE FWS-*A20F and FWS-*A20FI](#)

[UKCA FWS-*A20F and FWS-*A20FI](#)

AC

Rated voltage AC

1400 V

Rated voltage DC

1000 V

Color

None

Interrupt rating

50 kA at 1000 Vdc

Construction size

Other

Material

Ceramic

Packaging type

Standard

Voltage rating

1400 V

Fuse type

FWS-A20FI

Suitable for

CH127 Fuse holder



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)