

Eaton FWX-15A14F

Catalog Number: FWX-15A14F

Eaton Bussmann series FWX high speed fuse, 15A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWX-15A14F
	UPC
	051712795579
EAN	Product Length/Depth
5027590501347	55 mm
Product Height	Product Width
32 mm	73 mm
Product Weight	Warranty
22.4 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

1500 A

Accessories

CH14 Modular fuse holder
FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I²T)

83 at 250 V

Watt losses

3.8 W

Fuse shape

Cylindrical

Pre arc (I²T)

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Technical data sheets

[720006 FWX](#)

14

Interrupt rating

200 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

700 V

Fuse type

FWX-A14F



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)