

Eaton FWX-20A14F

Catalog Number: FWX-20A14F

Eaton Bussmann series FWX high speed fuse, 600V, 20A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

| | |
|---|-----------------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series high speed cylindrical fuse | FWX-20A14F |
| | UPC |
| | 051712795586 |
| EAN | Product Length/Depth |
| 5027590501361 | 55 mm |
| Product Height | Product Width |
| 32 mm | 73 mm |
| Product Weight | Warranty |
| 20.3 g | Not Applicable |
| Compliances | Certifications |
| CE Marked | UL Recognized |
| RoHS Compliant | |



defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

2000 A

Accessories

CH14 Modular fuse holder
FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I²T)

200 at 250 V

Watt losses

4.6 W

Fuse shape

Cylindrical

Pre arc (I²T)

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Installation videos

[Eaton's Switch disconnectors and Bussmann series fuses for MOEM Applications \(brightcove.net\)](#)

Technical data sheets

[720006 FWX](#)

Interrupt rating

200 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

690 V

Fuse type

FWX-A14F



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia