Eaton FWX-50A14F

Catalog Number: FWX-50A14F

Eaton Bussmann series FWX high speed fuse, 600V, 50A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end





Eaton Bussmann series high speed

cylindrical fuse

051712666213

EAN

5027590501422

Product Height

14 mm

Product Weight

9 g

Compliances

CE Marked

RoHS Compliant

Catalog Number

FWX-50A14F

UPC

Product Length/Depth

14 mm

Product Width

51 mm

Warranty

Not Applicable

Certifications

UL Recognized



default Taxonomy Attribute Label

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power 4 A Accessories FW14-PCB Breaking capacity 200 kA 62 Hz

converters/rectifiers

Amperage Rating

CH14 Modular fuse holder

Frequency rating - max

Frequency rating - min

45 Hz

Fuse indicator

Non Indicating

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I2T)

1800 at 250 V

Watt losses

5.7 W

Fuse shape

Cylindrical

Pre arc (I2T)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Technical data sheets

720006 FWX

Interrupt rating

200 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

700 V

Fuse type

FWX-A14F



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

