



Fuse-link, high speed, 240 A, AC 800 V, BS88, 80 x 180 mm, aR, BS, ultra rapid

Part no. GSMJ 240A 800V AC FUSE LINK- SFE8340240
Catalog No. GSMJ240

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	240
Rated voltage			AC 800 V
Construction size			BS88
Size			80 x 180 mm
Utilization category			aR
Breaking Capacity		kA	100
usable for size/applications			Protection of semi-conductor devices
Release characteristic	class		ultra rapid
Standard/Approval			BS
Shape			offset bolted tags
Standards/Regulations			BS88-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	240
Rated voltage		V	800
Voltage type			AC
Rated switching capacity		kA	100
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No