

Eaton LP-CC-3

Catalog Number: LP-CC-3

Eaton Bussmann series LP-CC fuse, Current-limiting time-delay fuse, Rejection style, 3 A, Dual, CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 20 kAIC at 150 Vdc|200 kAIC at 600 V, Melamine tube, Standard



General specifications

| | |
|----------------------------------|----------------|
| Product Name | Catalog Number |
| Eaton Bussmann series LP-CC fuse | LP-CC-3 |
| UPC | EAN |
| 051712180290 | 5027590446990 |
| Product Length/Depth | Product Height |
| 0.41 in | 1.5 in |
| Product Width | Product Weight |
| 0.41 in | 0.15 lb |
| Warranty | Compliances |
| Not Applicable | CE Marked |
| | RoHS Compliant |

defaultTaxonomyAttributeLabel

Type

Current-limiting time-delay fuse

Special features

Rejection style

Application

Specialized circuits and industrial control

Amperage Rating

3 A

Number of elements

Dual

Class

Class CC

Interrupt rating

200 kAIC at 600 Vac

20 kAIC at 150 Vdc

Fuse indicator

Non-indicating

Connection

Ferrule end x ferrule end

Response time

12 sec at 200%

Material

Melamine tube

Packaging type

Standard

Quantity

10

Voltage rating

600 Vac, 150 Vdc

Resources

Catalogs

[LP-CC-3~LOW PEAK CC TIME DELAY](#)

[Bussmann series complete full line catalog no. 1007](#)

Multimedia

[Bussmann series Fuseology](#)

Specifications and datasheets

[Eaton Specification Sheet - LP-CC-3](#)

Technical service bulletins

[Datasheet - FNQ-30](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)