

# Eaton LPJ-5SP

Catalog Number: LPJ-5SP

Eaton Bussmann series LPJ fuse, 5 A, Dual, Class J, Non-indicating, Ferrule end x ferrule end, Time delay|Current-limiting, 10 sec at 500%, 100 kAIC Vdc|300 kAIC at 600 V, Standard



Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series LPJ fuse	LPJ-5SP
<b>UPC</b>	<b>Product Length/Depth</b>
051712522823	2.25 in
<b>Product Height</b>	<b>Product Width</b>
0.81 in	0.81 in
<b>Product Weight</b>	<b>Warranty</b>
0.19 lb	Not Applicable
<b>Compliances</b>	
CE Marked	
RoHS Compliant	

## Electrical rating

### Amperage Rating

5 A

### Interrupt rating

100 kAIC Vdc

300 kAIC at 600 Vac

### Response time

10 sec at 500%

### Voltage rating

600 Vac, 300 Vdc

## Physical details

### Fuse type

Time delay

Current-limiting

### Number of elements

Dual

### Packaging type

Standard

## General information

### Class

Class J

### Connection

Ferrule end x ferrule end

### Fuse indicator

Non-indicating

### Special features

Non-indicating, High in-rush current motor protection

## Resources

### Catalogs

[LPJ-5SP~LOW-PEAK CLASS J T/D](#)

[Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses](#)

[Bussmann series complete full line catalog no. 1007](#)

### Multimedia

[Bussmann series Fuseology](#)

### Specifications and datasheets

[Eaton Specification Sheet - LPJ-5SP](#)

### Technical service bulletins

[Datasheet - FNQ-30](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)