

# Eaton NITD2

Catalog Number: NITD2

Fuse-link, LV, 2 A, AC 550 V, BS88/A1, 14 x 55 mm, gL/gG, BS



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage british standard fuse	NITD2
	<b>UPC</b>
	051712840064
<b>EAN</b>	<b>Product Length/Depth</b>
5027590504010	55 mm
<b>Product Height</b>	<b>Product Width</b>
14 mm	14 mm
<b>Product Weight</b>	<b>Warranty</b>
15.5 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
RoHS Compliant	IEC 60269-2
CE Marked	BS88

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

general industrial applications

### Amperage Rating

2 A

### Fitted with:

Offset bolted tags

### Fuse size

BS88/A1

### Current type

AC

### Mounting dimension

M4

### Center-to-center distance of connections

42.5 mm

### Breaking capacity

80 kA

### Rated switching capacity

80 kA

### Rated voltage AC

550 V

### Class

Class gG/gL

### Fuse type

NITD

### Utilization category

gL/gG (cable protection/equipment protection)

### Color

None

### Interrupt rating

80 kAIC

### Fuse indicator

None

### Insulated metal gripping lugs (IMGL)

## Resources

### Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

### Compliance information

CE AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

UKCA AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

### Multimedia

Eaton Bussmann - Red Spot fuse links

### Technical data sheets

4106 NITD fuses

No

Watt losses

0.9 W

Connection

Bolt-on

Construction

BS88/A1

Construction size

A1

Fuse shape

Offset slotted bolted tags

Voltage type

AC

Suitable for

CM32FC Camaster fuse holder

RS20 Red spot fuse holder

Voltage rating

550 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)