

# Eaton NON-20

Catalog Number: NON-20

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 20 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 250 Vac|50 kAIC at 125 Vdc, Standard, 10, 250 V, 125 Vdc

## General specifications



Photo is representative

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series NON fuse	NON-20
<b>UPC</b>	<b>Product Length/Depth</b>
051712101578	2 in
<b>Product Height</b>	<b>Product Width</b>
0.56 in	0.56 in
<b>Product Weight</b>	<b>Warranty</b>
0.036 lb	Not Applicable
<b>Compliances</b>	
CE Marked	

## Electrical rating

### Amperage Rating

20 A

### Interrupt rating

50 kAIC at 125 Vdc

50 kAIC at 250 Vac

### Voltage rating

250 Vac, 125 Vdc

## Physical details

### Packaging type

Standard

## General information

### Class

Class H

### Connection

Ferrule end x ferrule end

### Fuse indicator

Non-indicating

### Quantity

10

### Special features

Non current limiting

## Resources

### Catalogs

NON-20-BUSS ONE TIME FUSE

Bussmann series complete full line catalog no. 1007

### Multimedia

Bussmann series Fuseology

### Specifications and datasheets

Eaton Specification Sheet - NON-20

### Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)