Eaton NON-4

Catalog Number: NON-4

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 4 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 250 Vac|50 kAIC at 125 Vdc, Standard, 10, 250 V, 125 Vdc

General specifications

Product Name

Catalog Number

Eaton Bussmann series NON fuse

NON-4

UPC

EAN

051712300049

5027590065399

Product Length/Depth 0.56 in

Product Height

2 in

Product Width

Product Weight

0.56 in

0.35 lb

Warranty

Compliances

Not Applicable

CE Marked

Photo is representative



Electrical rating

Amperage Rating

4 A

Interrupt rating

50 kAIC at 250 Vac 50 kAIC at 125 Vdc

Voltage rating

250 Vac, 125 Vdc

Physical details

Packaging type

Standard

General information

Class

Class H

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Quantity

10

Special features

Non current limiting

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - NON-4

Technical data sheets

NON-4~BUSS ONE TIME FUSE

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia