# Eaton NON-40

# Catalog Number: NON-40

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 40 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 250 Vac|50 kAIC at 125 Vdc, Standard, 10, 250 V, 125 Vdc

## General specifications

**Product Name** 

Eaton Bussmann series NON fuse

**UPC** 

051712101615

Product Height

0.81 in

**Product Weight** 

0.01 lb

Compliances

CE Marked

Catalog Number

NON-40

Product Length/Depth

3 in

Product Width

0.81 in

Warranty

Not Applicable

Photo is representative



# Electrical rating

#### Amperage Rating

40 A

#### Interrupt rating

50 kAIC at 250 Vac 50 kAIC at 125 Vdc

#### Voltage rating

250 Vac, 125 Vdc

# Physical details

#### Packaging type

Standard

## General information

#### Class

Class H

#### Connection

Ferrule end x ferrule end

#### Fuse indicator

Non-indicating

#### Quantity

10

#### Special features

Non current limiting

#### Resources

#### Catalogs

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Bussmann series complete full line catalog no. 1007

#### Multimedia

Bussmann series Fuseology

## Specifications and datasheets

Eaton Specification Sheet - NON-40

#### Technical data sheets

NON-40~BUSS ONE TIME FUSE

#### Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia