

Eaton OSD100

Catalog Number: OSD100

Fuse-link, LV, 100 A, AC 500 V, BS88, 21 x 95 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	OSD100
	UPC
	051712840378
EAN	Product Length/Depth
5027590505086	95 mm
Product Height	Product Width
21 mm	21 mm
Product Weight	Warranty
55.75 g	Not Applicable
Compliances	
RoHS Compliant	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

100 A

Fitted with:

Offset bolted tags

Current type

AC

Mounting dimension

M5

Center-to-center distance of connections

73.5 mm

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

OSD

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

Resources

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

CE DEO OSD motor start

UKCA DEO OSD motor start

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4107 OSD fuses

8.5 W

Connection

74 mm Fixing Centre

Construction

BS88

Construction size

Other

Fuse shape

Offset bolted tags

Voltage type

AC

Suitable for

CM100F Red spot fuse holder

SC100 Safeclip fuse holder

Voltage rating

500 V

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)