

Eaton STD16

Catalog Number: STD16

Fuse-link, LV, 16 A, AC 240 V, BS88, 12 x 47 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	STD16
	UPC
	051712844666
EAN	Product Length/Depth
5027590512589	47 mm
Product Height	Product Width
13 mm	12 mm
Product Weight	Warranty
10 g	Not Applicable
Compliances	Certifications
CE Marked	BS88
RoHS Compliant	IEC 60269

defaultTaxonomyAttributeLabel

Type

Fuse

Application

street lighting cut-outs

Amperage Rating

16 A

Fitted with:

Offset bolted tags

Current type

AC

Mounting dimension

M4

Center-to-center distance of connections

35 mm

Breaking capacity

33 kA

Rated switching capacity

33 kA

Rated voltage AC

240 V

Class

Class gG/gL

Fuse type

STD

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

33 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

Resources

Catalogs

CA134002EN

STD16~Eaton Bussmann series low voltage British standard fuse

Bussmann series complete full line catalog no. 1007

Compliance information

CE Industrial offset blade tag and cylindrical fuse-links

UKCA Industrial offset blade tag and cylindrical fuse-links

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4123 STD fuses

1.5 W

Connection

Bolt-on

Construction

BS88

Construction size

Other

Fuse shape

Offset slotted bolted tags

Voltage type

AC

Voltage rating

240 V

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)