# Eaton TCF100

Bussmann

O

TCF100

## Catalog Number: TCF100

Eaton Bussmann series TCF fuse, 100 A, 60 Hz, 50 Hz, Dual, CF, Black, With indicator, Time delay, 10 sec at 500%, 300 kAIC at 600 V|100 kAIC at 300 Vdc, Glass filled PES, 35 mm DIN rail|Chassis, 600 V, 300 Vdc

#### General specifications



Eaton Bussmann series TCF fuse

**UPC** 

051712618182

Product Length/Depth

3.01 in

**Product Width** 

1 in

Warranty

Not Applicable

Certifications

UL Listed
CSA Certified

Catalog Number

TCF100

EAN

5027590244091

**Product Height** 

2.125 in

**Product Weight** 

0.284 lb

Compliances

CE Marked

**RoHS Compliant** 



### Electrical rating

Amperage Rating

100 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

100 kAIC at 300 Vdc 300 kAIC at 600 Vac

Response time

10 sec at 500%

Voltage rating

600 Vac, 300 Vdc

### Physical details

Color

Black

Fuse type

Class CF

Time delay

Material

Glass filled PES

Number of elements

Dual

Packaging type

Standard

#### General information

Class

Class CF

Connection

Blade end

Fuse indicator

With Indicator

Mounting method

Chassis

35 mm DIN rail

Special features

Finger safe

Used with

TCFH100N, CCP2-3-100CF

#### Resources

#### Catalogs

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Multimedia

Bussmann series Fuseology

The Power of Space

#### Specifications and datasheets

Eaton Specification Sheet - TCF100

Technical data sheets

TCF100~CUBEFUSE, TCF 100A IND

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia