Bussmann^{*}

690VAC OR LESS

TCF20RNW

TEST POINT

Eaton TCF20RNW

Catalog Number: TCF20RNW

Eaton Bussmann series TCF fuse, 20 A, 60 Hz, 50 Hz, Dual, Class CF, Black, Non-indicating, Blade end, Class CF|Time delay, 10 sec at 500%, 50 kAIC, Glass filled PES, Chassis|35 mm DIN rail, Standard, 690 V





Eaton Bussmann series TCF fuse

UPC

051712357203

Product Height

1.75 in

Product Weight

0.08 lb

Compliances

CE Marked RoHS Compliant Catalog Number

TCF20RNW

Product Length/Depth

1.88 in

Product Width

0.75 in

Warranty

Not Applicable

Certifications

UL Listed
CSA Certified



Electrical rating

Amperage Rating

20 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

50 kAIC

Response time

10 sec at 500%

Voltage rating

690 Vac

Physical details

Color

Black

Fuse type

Class CF

Time delay

Material

Glass filled PES

Number of elements

Dual

Packaging type

Standard

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Mounting method

Chassis

35 mm DIN rail

Special features

Finger safe

Used with

TCFH30NW

Resources

Catalogs

TCF20RNW~CUBEFUSE, TCFRNW 20A NON-IND

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - TCF20RNW



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia