Eaton TCF40

Bussmann

TCF40

Catalog Number: TCF40

Eaton Bussmann series TCF fuse, 40 A, 60 Hz, 50 Hz, Dual, CF, Black, Blade end, Time delay|Class CF, 10 sec at 500%, 100 kAlC at 300 Vdc|300 kAlC at 600 V, Glass filled PES, 35 mm DIN rail|Chassis, 600 V, 300 Vdc

General specifications



Eaton Bussmann series TCF fuse

UPC

051712615051

Product Length/Depth

2.13 in

Product Width

1 in

Warranty

Not Applicable

Certifications

UL Listed
CSA Certified

Catalog Number

TCF40

EAN

5027590116992

Product Height

1.9 in

Product Weight

0.17 lb

Compliances

CE Marked

RoHS Compliant



Electrical rating

Amperage Rating

40 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

100 kAIC at 300 Vdc 300 kAIC at 600 Vac

Response time

10 sec at 500%

Voltage rating

600 Vac, 300 Vdc

Physical details

Color

Black

Fuse type

Class CF

Time delay

Material

Glass filled PES

Number of elements

Dual

Packaging type

Standard

General information

Class

Class CF

Connection

Blade end

Fuse indicator

With Indicator

Mounting method

Chassis

35 mm DIN rail

Special features

Finger safe

Used with

TCFH60N, CCP2-3-60CF

Resources

Multimedia

Bussmann series Fuseology

The Power of Space

Specifications and datasheets

Eaton Specification Sheet - TCF40

Technical data sheets

TCF40~CUBEFUSE, TCF 40A IND

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia