



## CJ1W-ID262

Digital input unit, 64 x 24 VDC inputs, MIL40 connector (not included)

# Specifications

I/O system	CJ I/O Bus
Expansion unit type	Basic I/O Unit
Type of module	Digital I/O
Number of digital inputs	64
Digital input type	PNP/NPN
Permitted voltage at input	20.4-26.4 V
OFF/ON delay	0-32 ms
Number of digital outputs	0
Digital output type	None
Output current	0 A
Short-circuit protected outputs	✘
I/O connection type	MIL (plug not included)
Number of I/O connectors	2
Detachable I/O connector	✔
Suitable for safety functions	✘
Number of IOV (V+) terminals	0
Number of IOG (V-) terminals	0
Number of COM terminals	8
Product Height (unpacked)	90 mm
Product Width (unpacked)	31 mm
Product Depth (unpacked)	83.6 mm
Product Weight (unpacked)	96 g

# Accessories



**G70V-SID16P**

Relay terminal, PLC Input, 16 channels, NPN, Push-in terminals



**G70V-SID16P-1**

Relay terminal, PLC Input, 16 channels, PNP, Push-in terminals

**P2RV-4-100IMC**

G2RV interface cable for use between CJ1W-ID233/ID262 and 4 P2RV-8-I-F modules, 1 m

**P2RV-4-200IMC**

G2RV interface cable for use between CJ1W-ID233/ID262 and 4 P2RV-8-I-F modules, 2 m



**P2RVC-8ST-I-5**

Interface unit for G2RV-SR/G3RV-ST Push-in, PLC Input, 8 channels, NPN, 30 VAC/DC, Total 2 A, Push-in



**P2RVC-8ST-I-5-1**

Interface unit for G2RV-SR/G3RV-ST Push-in, PLC Input, 8 channels, PNP, 30 VAC/DC, Total 2 A, Push-in



**P2RVC-8ST-I-7-1**

Interface unit for G2RV-SR/G3RV-ST Screw, PLC Input, 8 channels, PNP, 30 VAC/DC, Total 2 A, Rising-up screw



**XW2D-40G6**

General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points



**XW2K-40G-O32C**

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting



**XW2Z-0030FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 0.3 m



**XW2Z-0050FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 0.5 m



**XW2Z-0100FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 1 m



**XW2Z-0100FH-L02**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 1 m



**XW2Z-0100FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 1 m



**XW2Z-0150FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 1.5 m



**XW2Z-0150FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 1.5 m



**XW2Z-0200FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 2 m



**XW2Z-0200FH-L02**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 2 m



**XW2Z-0200FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 2 m



**XW2Z-0300FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 3 m



**XW2Z-0300FH-L02**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 3 m



**XW2Z-0300FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 3 m



**XW2Z-0500FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 5 m



**XW2Z-0500FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 5 m



**XW2Z-100K**

I/O connection cable, MIL40 to MIL40, 1 m



**XW2Z-150K**

I/O connection cable, MIL40 to MIL40, 1.5 m



**XW2Z-200K**

I/O connection cable, MIL40 to MIL40, 2 m



**XW2Z-300K**

I/O connection cable, MIL40 to MIL40, 3 m



**XW2Z-500K**

I/O connection cable, MIL40 to MIL40, 5 m



**XW2Z-C50K**

I/O connection cable, MIL40 to MIL40, 0.5 m



**XW2Z-RO100-75-D1**

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 1 m



**XW2Z-RO200-175-D1**

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 2.0 m and 1.75 m



**XW2Z-RO75-50-D1**

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 0.75 m

## Downloads

### CAD Library



#### **CJ1W-ID/IA Datasheet**

**EN** PDF 3.3 MB



#### **CJ2 CPU Units Hardware Users Manual**

**EN** PDF 8.4 MB



#### **CJ2-Series Programmable Controller**

**Datasheet**

**EN** PDF 17.3 MB



#### **EAC Mark removal Discontinuation Notice**

**EN** PDF 221 KB

