



## CJ1W-OD232

Digital output unit, 32 x transistor outputs, PNP, 0.5 A, 24 VDC, load short-circuit protection, MIL40 connector (not included)

# Specifications

I/O system	CJ I/O Bus
Expansion unit type	Basic I/O Unit
Type of module	Digital I/O
Number of digital inputs	0
Digital input type	None
OFF/ON delay	2-8 ms
Number of digital outputs	32
Digital output type	PNP
Permitted voltage at output	20.4-26.4 V
Output current	0.5 A
Short-circuit protected outputs	✘
I/O connection type	MIL (plug not included)
Number of I/O connectors	1
Detachable I/O connector	✔
Suitable for safety functions	✘
Number of IOV (V+) terminals	2
Number of IOG (V-) terminals	2
Number of COM terminals	0
Product Height (unpacked)	90 mm
Product Width (unpacked)	20 mm
Product Depth (unpacked)	83.6 mm
Product Weight (unpacked)	70 g



**G70A-ZOC16-4 DC24**

Output Terminal Block for Relay or SSR, 16-point, for PNP output units



**G70V-SOC16P-1**

Relay terminal, PLC Output, 16 channels, PNP, Push-in terminals



**P2RV-4-100C**

G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 1 m



**P2RV-4-200C**

G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 2 m



**P2RV-4-300C**

G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 3 m



**P2RVC-8ST-O-5-1**

Interface unit for G2RV-SR/G3RV-ST Push-in, PLC Output, 8 channels, PNP, 30 VAC/DC, Total 2 A, Push-in



**P2RVC-8ST-O-7-1**

Interface unit for G2RV-SR/G3RV-ST Screw, PLC Output, 8 channels, PNP, 30 VAC/DC, Total 2 A, Rising-up screw



**XW2D-40G6**

General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points



**XW2K-40G-O32C**

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting



**XW2Z-0030FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 0.3 m



**XW2Z-0050FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 0.5 m



**XW2Z-0100FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 1 m



**XW2Z-0100FH-L02**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 1 m



**XW2Z-0100FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 1 m



**XW2Z-0150FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 1.5 m



**XW2Z-0150FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 1.5 m



**XW2Z-0200FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 2 m



**XW2Z-0200FH-L02**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 2 m



**XW2Z-0200FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 2 m



**XW2Z-0300FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 3 m



**XW2Z-0300FH-L02**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 3 m



**XW2Z-0300FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 3 m



**XW2Z-0500FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 5 m



**XW2Z-0500FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 5 m



**XW2Z-100K**

I/O connection cable, MIL40 to MIL40, 1 m



**XW2Z-150K**

I/O connection cable, MIL40 to MIL40, 1.5 m



**XW2Z-200K**

I/O connection cable, MIL40 to MIL40, 2 m



**XW2Z-300K**

I/O connection cable, MIL40 to MIL40, 3 m



**XW2Z-500K**

I/O connection cable, MIL40 to MIL40, 5 m



**XW2Z-C50K**

I/O connection cable, MIL40 to MIL40, 0.5 m



**XW2Z-RO100-75-D1**

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 1 m



**XW2Z-RO200-175-D1**

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 2.0 m and 1.75 m



**XW2Z-RO75-50-D1**

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 0.75 m

## Downloads

CAD Library



**CJ1W-OC/OA/OD**  
**Datasheet**

EN PDF 3.88 MB



**CJ2 CPU Units Hardware**  
**Users Manual**

EN PDF 8.4 MB



**CJ2-Series**  
**Programmable**  
**Controller**  
**Datasheet**

EN PDF 17.3 MB



**EAC Mark removal**  
**Discontinuation Notice**

EN PDF 221 KB

