



## CJ1W-OD261

Digital output unit, 64 x transistor outputs, NPN, 0.5 A, 12 to 24 VDC, 2 x FCN40 connectors (not included)

# Specifications

|                                 |                         |
|---------------------------------|-------------------------|
| I/O system                      | CJ I/O Bus              |
| Expansion unit type             | Basic I/O Unit          |
| Type of module                  | Digital I/O             |
| Number of digital inputs        | 0                       |
| Digital input type              | None                    |
| Number of digital outputs       | 64                      |
| Digital output type             | NPN                     |
| Permitted voltage at output     | 10.2-26.4 V             |
| Output current                  | 0.3 A                   |
| Short-circuit protected outputs | ✘                       |
| I/O connection type             | FCN (plug not included) |
| Number of I/O connectors        | 2                       |
| Detachable I/O connector        | ✔                       |
| Suitable for safety functions   | ✘                       |
| Number of IOV (V+) terminals    | 8                       |
| Number of IOG (V-) terminals    | 8                       |
| Number of COM terminals         | 0                       |
| Product Height (unpacked)       | 90 mm                   |
| Product Width (unpacked)        | 31 mm                   |
| Product Depth (unpacked)        | 66.5 mm                 |
| Product Weight (unpacked)       | 110 g                   |

# Accessories




**G70A-ZOC16-3 DC24**

Output Terminal Block for Relay or SSR, 16-point, for NPN output units



**XW2D-40G6**

General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points



**XW2K-40G-O32B**

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting



**XW2K-40G-O32B-OUT**

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Output, Signal: 0.5 A, Power: 7 A, NPN, 30 VDC, DIN rail horizontal and vertical mounting



**XW2Z-0100BF-L**

I/O connection cable, unshielded, FCN40 to MIL40, 1 m



**XW2Z-0100BH-L02**

I/O connection cable, unshielded, FCN40 to 2 x MIL20, 1 m, cross-wired



**XW2Z-0100BN-L**

I/O connection cable, unshielded, FCN40 to open ends, 1 m



**XW2Z-0200BF-L**

I/O connection cable, unshielded, FCN40 to MIL40, 2 m



**XW2Z-0200BH-L02**

I/O connection cable, unshielded, FCN40 to 2 x MIL20, 2 m, cross-wired



**XW2Z-0200BN-L**

I/O connection cable, unshielded, FCN40 to open ends, 2 m



**XW2Z-0300BN-L**

I/O connection cable, unshielded, FCN40 to open ends, 3 m



**XW2Z-050B**

I/O connection cable, FCN40 to MIL40, 0.5 m



**XW2Z-100B**

I/O connection cable, FCN40 to MIL40, 1 m



**XW2Z-150B**

I/O connection cable, FCN40 to MIL40, 1.5 m



**XW2Z-200B**

I/O connection cable, FCN40 to MIL40, 2 m



**XW2Z-300B**

I/O connection cable, FCN40 to MIL40, 3 m



**XW2Z-RO100C-75**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70A-ZOC16-3, 1 m / 0.75 m



**XW2Z-RO150C-125**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70A-ZOC16-3, 1.5 m / 1.25 m



**XW2Z-RO200C-150**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70A-ZOC16-3, 2 m / 1.5 m



**XW2Z-RO200C-175**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70 A-ZOC16-3, 2 m / 1.75 m

## Downloads

### CAD Library



#### **CJ1W-OC/OA/OD Datasheet**

**EN** PDF 3.88 MB



#### **CJ2 CPU Units Hardware Users Manual**

**EN** PDF 8.4 MB



#### **CJ2-Series Programmable Controller**

**Datasheet**

**EN** PDF 17.3 MB



#### **EAC Mark removal Discontinuation Notice**

**EN** PDF 221 KB

