



# CK3E-1210

Programmable Multi-Axis Controller  $\mu$ Power PMAC, 8 axes

# Specifications

Max. number of synchronous axes	8
Communication port(s)	EtherCAT Master, Ethernet TCP/IP, USB
Supply voltage DC	20.4-26.4 V
Product Height (unpacked)	125 mm
Product Width (unpacked)	28.6 mm
Product Depth (unpacked)	170.9 mm
Product Weight (unpacked)	700 g

# Downloads

## CAD Library



### CK3E Programmable Multi-Axis Controller Datasheet

EN PDF 1.42 MB



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### NJ-series -[EtherNet/IP]- CK3M-CPU1x1 Connection Guide

EN PDF 3.88 MB



### Programmable Multi-Axis Controller Brochure

EN PDF 7.81 MB



### Programmable Multi-Axis Controller Users Manual

EN PDF 2.05 MB



### Startup Guide Getting Started Guide

EN PDF 3.88 MB



### Startup Guide For EtherCAT® Communication Coupler Getting Started Guide

EN PDF 6.16 MB



### Startup Guide for 1S-Series Servo Drive (IDEv4) Getting Started Guide

EN PDF 5.26 MB



### Startup Guide for 1S-series Servo Drives Getting Started Guide

EN PDF 6 MB

