



DRT2-ID16

DeviceNet digital input unit, 16 x inputs, 24 VDC, NPN, screw terminal block

Specifications

Communication port(s)	DeviceNet Slave
Type of module	Digital I/O
I/O connection type	Screw
Connection method	1-wire
Number of digital inputs	16
Digital input type	NPN
Permitted voltage at input	0-26.4 V
Number of digital outputs	0
Digital output type	None
Short-circuit protected outputs	✘
I/O system	I/O Expansion Link
Degree of protection (IP)	IP20
Product Height (unpacked)	50 mm
Product Width (unpacked)	115 mm
Product Depth (unpacked)	49.7 mm
Product Weight (unpacked)	150 g

Accessories



DCN1-3C

DeviceNet T-branch tap for 3 branch lines, 5 connectors with screws, side cable entry



DCN1-3NC

DeviceNet T-Branch tap for 3 branch lines, 5 parallel clamp connectors, top cable entry



DRS1-T

CompoNet/DeviceNet termination terminal block



XW4G-05C4-TF-D

DeviceNet connector, multi-branch parallel screwless, connector insertion and wiring in same direction.

Downloads

CAD Library



DRT2-AD04/-DA02
Discontinuation Notice

EN PDF 279 KB



DRT2/CS1/CJ1/C200HW/CVM56/CPM1A/CPM2A/CPM2B/CPM2C/CPM2L/DCN1/DCN2
DeviceNet
Brochure

EN PDF 30.4 MB



EN PDF 471 KB



DeviceNet
Operation Manual

EN PDF 3.61 MB



DeviceNet Smart Slaves
Datasheet

EN PDF 2.89 MB



EAC Mark removal
Discontinuation Notice

EN PDF 221 KB



Relay Output Remote I/O Terminal
Leaflet

EN PDF 606 KB



Remote I/O Terminals
Brochure

EN PDF 1.72 MB

