

DRT2-ROS16

DeviceNet digital output unit, 16 x relay outputs, 3A, 240 VAC, 24 VDC, screw terminal block

Specifications

Communication port(s)	DeviceNet Slave
Type of module	Digital I/O
I/O connection type	Screw
Connection method	1-wire
Number of digital inputs	0
Digital input type	None
Number of digital outputs	16
Digital output type	Relay NO
Permitted voltage at output	0-250 V
Output current	3 A
Short-circuit protected outputs	✘
I/O system	I/O Expansion Link
Degree of protection (IP)	IP20
Product Height (unpacked)	50 mm
Product Width (unpacked)	125 mm
Product Depth (unpacked)	51.8 mm
Product Weight (unpacked)	260 g



DCN1-3C

DeviceNet T-branch tap for 3 branch lines, 5 connectors with screws, side cable entry



DCN1-3NC

DeviceNet T-Branch tap for 3 branch lines, 5 parallel clamp connectors, top cable entry



DRS1-T

CompoNet/DeviceNet termination terminal block



XW4G-05C4-TF-D

DeviceNet connector, multi-branch parallel screwless, connector insertion and wiring in same direction.



XWT-ID08-1

CRT1/DRT2/GX-series I/O expansion unit, 8 x 24 VDC inputs, PNP (1 max per I/O terminal, specific models only)



XWT-ID16-1


CRT1/DRT2/GX-series I/O expansion unit, 16 x 24 VDC inputs, PNP (1 max per I/O terminal, specific models only)



XWT-OD16-1

CRT1/DRT2/GX-series I/O expansion unit, 16 x 24 VDC outputs, 0.5 A, PNP (1 max per I/O terminal, specific models only)

CAD Library



DRT2-AD04/-DA02 Discontinuation Notice

EN PDF 279 KB



DRT2/CS1/CJ1/C200HW/CVM56/CPM1A/CPM2A/CPM2B/CPM5A/CPM5B/DCN1/DCN2 DeviceNet Brochure

EN PDF 30.4 MB



DRT2/CS1/CJ1/C200HW/CVM56/CPM1A/CPM2A/CPM2B/CPM5A/CPM5B/DCN1/DCN2 Brochure

EN PDF 471 KB



DeviceNet Operation Manual

EN PDF 3.61 MB



DeviceNet Smart Slaves Datasheet

EN PDF 2.89 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Relay Output Remote I/O Terminal Leaflet

EN PDF 606 KB



Remote I/O Terminals Brochure

EN PDF 1.72 MB