



## E3T-FL13 2M

Photoelectric sensor, background suppression, 1-15mm, DC, 3-wire, PNP, light-on, flat, 2m cable (requires bracket)

# Specifications

|                           |                         |
|---------------------------|-------------------------|
| Shape                     | Cuboid, M2 mounting     |
| Sensing method            | Background suppression  |
| Sensing distance          | 15 mm                   |
| Sensing distance (min.)   | 1 mm                    |
| Setting method            | Fixed                   |
| Connection method         | Cable                   |
| Cable length              | 2 m                     |
| Output type               | PNP                     |
| Operation mode            | Light-ON                |
| Response time             | 1 ms                    |
| Material housing          | PBT                     |
| Thread size               | Other                   |
| Product Width (unpacked)  | 12 mm                   |
| Product Height (unpacked) | 24 mm                   |
| Product Depth (unpacked)  | 3.5 mm                  |
| Type of light             | Polarity free red light |
| Power supply voltage      | 12-24 V                 |
| Degree of protection (IP) | IP67                    |

# Accessories



**E39-L120**

Mounting bracket for E3T-F\* sensor

CAD Library



**E3T Miniature Square Photoelectric Sensor, plastic housing**

**Datasheet**

**EN** PDF 6.7 MB



**EAC Mark removal Discontinuation Notice**

**EN** PDF 221 KB