



E3T-SL23 2M

Photoelectric sensor, diffuse, 30 mm, DC, 3-wire, PNP, light-on, side view, 2 m cable

Specifications

| | |
|----------------------------------|-------------------------|
| Shape | Cuboid, M2 mounting |
| Sensing method | Limited reflective |
| Sensing distance | 30 mm |
| Sensing distance (min.) | 5 mm |
| Setting method | Fixed |
| Connection method | Cable |
| Cable length | 2 m |
| Output type | PNP |
| Operation mode | Light-ON |
| Response time | 1 ms |
| Material housing | PBT |
| Thread size | Other |
| Product Width (unpacked) | 7 mm |
| Product Height (unpacked) | 24.5 mm |
| Product Depth (unpacked) | 11 mm |
| Type of light | Polarity free red light |
| Power supply voltage | 12-24 V |
| Degree of protection (IP) | IP67 |

Accessories



E39-L117

Mounting bracket for E3T-S* sensor, rear mounting



E39-L118

Mounting bracket for E3T-S* sensor, side mounting

Downloads

CAD Library



E3T Miniature Square Photoelectric Sensor, plastic housing

Datasheet

EN PDF 6.7 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB