



E3T-SL24 2M

Photoelectric sensor, convergent-reflective, miniature, side view, 5-30mm, D-on, PNP, 2m cable

Specifications

Shape	Cuboid, M2 mounting
Sensing method	Limited reflective
Sensing distance	30 mm
Sensing distance (min.)	5 mm
Setting method	Fixed
Connection method	Cable
Cable length	2 m
Output type	PNP
Operation mode	Dark-ON
Response time	1 ms
Material housing	PBT
Thread size	Other
Product Width (unpacked)	7 mm
Product Height (unpacked)	24.5 mm
Product Depth (unpacked)	11 mm
Type of light	Polarity free red light
Power supply voltage	12-24 V
Degree of protection (IP)	IP67

Accessories



E39-L117

Mounting bracket for E3T-S* sensor, rear mounting



E39-L118

Mounting bracket for E3T-S* sensor, side mounting

Downloads

CAD Library



E3T Miniature Square Photoelectric Sensor, plastic housing

Datasheet

EN PDF 6.7 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 1 February, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU