



G2R-1-S 240VAC (S)

Relay, plug-in, SPDT, 10 A, mechanical indicator, 240 VAC

Specifications

Mounting method	With plug-in socket
Usage	General purpose, Interface
Poles	1
Coil voltage	240 V
Rated carry current	10 A
Operation voltage	AC
Contact material	AgSnIn
Contact description	SPDT
Features	Transparent case, With mechanical indicator
Terminal	Plug-in

Fits to



P2RF-05-ESS

G2RS socket, 1-pole, DIN-rail/surface-mounting, screw (box type)



P2RF-05-PU

Socket, DIN rail/surface mounting, 15.5 mm, 5-pin, Push-in terminals



P2RF-05-S

Socket, DIN rail/surface mounting, 5-pin, screwless terminals



P2RFZ-05-E

Socket, DIN rail/surface mounting, 5-pin, screw terminals

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



G2R-_-S (S) General- purpose Relay Datasheet

EN PDF 3.9 MB



Industrial Relays Brochure

EN PDF 2.77 MB



OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



Panel Building Brochure

EN PDF 3.11 MB