

G2R-1-SN 120VAC (S)

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, 120 VAC

Specifications

Mounting method	With plug-in socket
Usage	General purpose, Interface
Poles	1
Coil voltage	120 V
Rated carry current	10 A
Operation voltage	AC
Contact material	AgSnIn
Contact description	SPDT
Features	LED, Transparent case, With mechanical indicator
Terminal	Plug-in

Fits to



P2RF-05-ESS

G2RS socket, 1-pole, DIN-rail/surface-mounting, screw (box type)



P2RF-05-PU

Socket, DIN rail/surface mounting, 15.5 mm, 5-pin, Push-in terminals



P2RF-05-S

Socket, DIN rail/surface mounting, 5-pin, screwless terminals



P2RFZ-05-E

Socket, DIN rail/surface mounting, 5-pin, screw terminals

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



G2R-_-S (S) General- purpose Relay Datasheet

EN PDF 3.9 MB



Industrial Relays Brochure

EN PDF 2.77 MB



OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



Panel Building Brochure

EN PDF 3.11 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 24 April, 2024. Click here for [terms of use](#).