



## G2R-1-SN 48VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, label facility, 48 VDC

# Specifications

Mounting method	With plug-in socket
Usage	General purpose, Interface
Poles	1
Coil voltage	48 V
Rated carry current	10 A
Operation voltage	DC
Contact material	AgSnIn
Contact description	SPDT
Features	LED, Transparent case, With mechanical indicator
Terminal	Plug-in

## Fits to



### P2RF-05-ESS

G2RS socket, 1-pole, DIN-rail/surface-mounting, screw (box type)



### P2RF-05-PU

Socket, DIN rail/surface mounting, 15.5 mm, 5-pin, Push-in terminals



### P2RF-05-S

Socket, DIN rail/surface mounting, 5-pin, screwless terminals



### P2RFZ-05-E

Socket, DIN rail/surface mounting, 5-pin, screw terminals

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### G2R-\_-S (S) General- purpose Relay Datasheet

EN PDF 3.9 MB



### Industrial Relays Brochure

EN PDF 2.77 MB



### OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



### Panel Building Brochure

EN PDF 3.11 MB