



G2R-2-SN 120VAC (S)

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 120 VAC

Specifications

| | |
|---------------------|--|
| Mounting method | With plug-in socket |
| Usage | General purpose, Interface |
| Poles | 2 |
| Coil voltage | 120 V |
| Rated carry current | 5 A |
| Operation voltage | AC |
| Contact material | AgSnIn |
| Contact description | DPDT |
| Features | LED, Transparent case, With mechanical indicator |
| Terminal | Plug-in |

Fits to



P2RF-08-ESS

G2RS socket, 2-pole, DIN-rail/surface-mounting, screw (box type)



P2RF-08-PU

Socket, DIN rail/surface mounting, 15.5 mm, 8-pin, Push-in terminals



P2RF-08-S

Socket, DIN rail/surface mounting, 8-pin, screwless terminals



P2RFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



G2R-_-S (S) General- purpose Relay Datasheet

EN PDF 3.9 MB



Industrial Relays Brochure

EN PDF 2.77 MB



OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



Panel Building Brochure

EN PDF 3.11 MB