



G2R-2-SNDI 48VDC (S)

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility

Specifications

Mounting method	With plug-in socket
Usage	General purpose, Interface
Poles	2
Coil voltage	48 V
Rated carry current	5 A
Operation voltage	DC
Contact material	AgSnIn
Contact description	DPDT
Features	Diode, LED, Test button, Transparent case, With mechanical indicator
Terminal	Plug-in

Fits to



P2RF-08-ESS

G2RS socket, 2-pole, DIN-rail/surface-mounting, screw (box type)



P2RF-08-PU

Socket, DIN rail/surface mounting, 15.5 mm, 8-pin, Push-in terminals



P2RF-08-S

Socket, DIN rail/surface mounting, 8-pin, screwless terminals



P2RFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



G2R-_-S (S) General- purpose Relay Datasheet

EN PDF 3.9 MB



Industrial Relays Brochure

EN PDF 2.77 MB



OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



Panel Building Brochure

EN PDF 3.11 MB