



GRT1-ID8-1

SmartSlice 8 x digital inputs, 24 VDC, PNP

Specifications

I/O system	GRT1 I/O Bus
Type of module	Digital I/O
I/O connection type	Push-in
Connection method	1-wire, 2-wire
Number of digital inputs	8
Digital input type	PNP
Permitted voltage at input	15-26.4 V
Number of digital outputs	0
Digital output type	None
Output current	0 A
Short-circuit protected outputs	✘
Number of IOV (V+) terminals	4
Number of IOG (V-) terminals	0
Degree of protection (IP)	IP20
Product Height (unpacked)	84 mm
Product Width (unpacked)	15 mm
Product Depth (unpacked)	74.4 mm
Product Weight (unpacked)	88 g

CAD Library



EtherCAT Junction Slave Brochure

EN PDF 1.04 MB



GRT1 series (Precautions For UL CSA Standards) Instruction Sheet

EN PDF 46.5 KB



GRT1 series (Safety Precautions) Instruction Sheet

EN PDF 522 KB



GRT1- SmartSlice Remote I/O Datasheet

EN PDF 446 KB



GRT1-series Discontinuation Notice

EN PDF 80.8 KB



SmartSlice Brochure

EN PDF 2.03 MB



Sysmac Catalogue

EN PDF 43.5 MB