



MY2-GS-R AC220/240

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 220/240 VAC

Specifications

Mounting method	With plug-in socket
Usage	General purpose
Poles	2
Rated carry current	10 A
Coil voltage	230 V
Operation voltage	AC
Contact material	Ag
Contact description	DPDT
Features	Transparent case, With mechanical indicator
Terminal	Plug-in, Solder

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 25 April, 2024. Click here for [terms of use](#).

Fits to



PY08-02

Socket, back-connecting, 8-pin, PCB terminals



PYF-08-PU

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



PYF-08-PU-L

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



PYF08A-N

Socket, DIN rail/surface mounting, 8-pin, screw terminals (IEC/VDE)



PYF08S

Socket, DIN rail mounting, 8-pin, screwless terminals



PYFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals (standard)

Downloads



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Industrial Relays Brochure

EN PDF 2.77 MB



MY-GS-R/MY(s)/MYK/MYQ/MYH Miniature Power Relays

Datasheet

EN PDF 5.49 MB



OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



Solution case study No.8 Environment resistance

Brochure

EN PDF 623 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 25 April, 2024. Click here for [terms of use](#).