



MY2-GS-R AC48

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 48 VAC

Specifications

Mounting method	With plug-in socket
Usage	General purpose
Poles	2
Rated carry current	10 A
Coil voltage	48 V
Operation voltage	AC
Contact material	Ag
Contact description	DPDT
Features	Transparent case, With mechanical indicator
Terminal	Plug-in, Solder

Fits to



PY08-02

Socket, back-connecting, 8-pin, PCB terminals



PYF-08-PU

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



PYF08A-N

Socket, DIN rail/surface mounting, 8-pin, screw terminals (IEC/VDE)



PYFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals (standard)



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Industrial Relays Brochure

EN PDF 2.77 MB



MY-GS- R/MY(s)/MYK/MYQ/MYH Miniature Power Relays Datasheet

EN PDF 5.49 MB



OMRON Manufacturing Know-How: High Quality Relays Leaflet

EN PDF 449 KB



Solution case study No.8 Environment resistance Brochure

EN PDF 623 KB