



MY2-GS-R DC12

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 12 VDC

Specifications

| | |
|----------------------------|---|
| Mounting method | With plug-in socket |
| Usage | General purpose |
| Poles | 2 |
| Rated carry current | 10 A |
| Coil voltage | 12 V |
| Operation voltage | DC |
| Contact material | Ag |
| Contact description | DPDT |
| Features | Transparent case, With mechanical indicator |
| Terminal | Plug-in, Solder |

Fits to



PY08-02

Socket, back-connecting, 8-pin, PCB terminals



PYF-08-PU

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



PYF-08-PU-L

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



PYF08A-N

Socket, DIN rail/surface mounting, 8-pin, screw terminals (IEC/VDE)



PYF08S

Socket, DIN rail mounting, 8-pin, screwless terminals



PYFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals (standard)

Downloads



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Industrial Relays Brochure

EN PDF 2.77 MB



MY-GS-R/MY(s)/MYK/MYQ/MYH Miniature Power Relays

Datasheet

EN PDF 5.49 MB



OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



Solution case study No.8 Environment resistance

Brochure

EN PDF 623 KB

