



## MY2IN-GS-R AC110/120

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

# Specifications

<b>Mounting method</b>	With plug-in socket
<b>Usage</b>	General purpose
<b>Poles</b>	2
<b>Rated carry current</b>	10 A
<b>Coil voltage</b>	110 V
<b>Operation voltage</b>	AC
<b>Contact material</b>	Ag
<b>Contact description</b>	DPDT
<b>Features</b>	LED, Test button, Transparent case, With mechanical indicator
<b>Terminal</b>	Plug-in, Solder



## **PY08-02**

Socket, back-connecting, 8-pin, PCB terminals



## **PYF-08-PU**

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



## **PYF-08-PU-L**

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



## **PYF08A-N**

Socket, DIN rail/surface mounting, 8-pin, screw terminals (IEC/VDE)



## **PYF08S**

Socket, DIN rail mounting, 8-pin, screwless terminals



## **PYFZ-08-E**

Socket, DIN rail/surface mounting, 8-pin, screw terminals (standard)

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### Industrial Relays Brochure

EN PDF 2.77 MB



### MY-GS- R/MY(s)/MYK/MYQ/MYH Miniature Power Relays Datasheet

EN PDF 5.49 MB



### OMRON Manufacturing Know-How: High Quality Relays Leaflet

EN PDF 449 KB



### Solution case study No.8 Environment resistance Brochure

EN PDF 623 KB