



MY2K-02 24VDC

Latching relay, pcb pins, 14-pin, DPDT, 3 A, LED indicator, 24 VDC

Specifications

Mounting method	With plug-in socket
Usage	General purpose
Poles	2
Rated carry current	3 A
Coil voltage	24 V
Operation voltage	DC
Contact material	Ag alloy + Au plating
Contact description	DPDT
Features	Au plating, Latching relay, Transparent case, With mechanical indicator
Terminal	PCB

Fits to



PYF-08-PU

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



PYF-08-PU-L

Socket, DIN rail/surface mounting, 31 mm, 8-pin, Push-in terminals



PYF08S

Socket, DIN rail mounting, 8-pin, screwless terminals



PYFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals (standard)

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Industrial Relays Brochure

EN PDF 2.77 MB



MYK General-purpose Latching Relay Datasheet

EN PDF 1.02 MB



OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



Solution case study No.8 Environment resistance

Brochure

EN PDF 623 KB