



## MY4H 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed

# Specifications

<b>Usage</b>	General purpose
<b>Poles</b>	4
<b>Rated carry current</b>	3 A
<b>Coil voltage</b>	120 V
<b>Operation voltage</b>	AC
<b>Contact material</b>	Ag alloy + Au plating
<b>Contact description</b>	4PDT
<b>Features</b>	Hermetically sealed
<b>Terminal</b>	Plug-in



## PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



## PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



## PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



## PYF14-ESS-B

Socket, with common, NC & NO terminals at the top and the coil terminals at the bottom - Black



## PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



## PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### Industrial Relays Brochure

EN PDF 2.77 MB



### MY(S) Miniature Power Relays Datasheet

EN PDF 9.29 MB



### OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



### Solution case study No.8 Environment resistance

Brochure

EN PDF 623 KB