



## MY4IN-GS-R AC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VAC

# Specifications

<b>Mounting method</b>	With plug-in socket
<b>Usage</b>	General purpose
<b>Poles</b>	4
<b>Rated carry current</b>	6 A
<b>Coil voltage</b>	24 V
<b>Operation voltage</b>	AC
<b>Contact material</b>	Ag
<b>Contact description</b>	4PDT
<b>Features</b>	LED, Test button, Transparent case, With mechanical indicator
<b>Terminal</b>	Plug-in, Solder



## PY14-02

Socket, back-connecting,  
14-pin, PCB terminals



## PYF-14-PU

Socket, DIN rail/surface  
mounting, 31 mm, 14-pin,  
Push-in terminals



## PYF-14-PU-L

Socket, DIN rail/surface  
mounting, 31 mm, 14-pin,  
Push-in terminals,



## PYF14-ESN-B

Socket, with common and  
coil terminals on the bottom  
and with the NC & NO  
terminal on the top - Black.



## PYF14-ESS-B

Socket, with common, NC &  
NO terminals at the top and  
the coil terminals at the  
bottom - Black



## PYF14A-N

Socket, DIN rail/surface  
mounting, 14-pin, screw  
terminals (IEC/VDE)



## PYF14S

Socket, DIN rail mounting,  
14-pin, screwless terminals



## PYFZ-14-E

Socket, DIN rail/surface  
mounting, 14-pin, screw  
terminals (standard)

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### Industrial Relays Brochure

EN PDF 2.77 MB



### MY-GS- R/MY(s)/MYK/MYQ/MYH Miniature Power Relays Datasheet

EN PDF 5.49 MB



### OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



### Solution case study No.8 Environment resistance

Brochure

EN PDF 623 KB