



## MY4Z 110/120VAC (S)

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 100/120 VAC

# Specifications

Mounting method	With plug-in socket
Rated carry current	3 A
Coil voltage	120 V
Operation voltage	AC
Contact material	Ag alloy + Au cladding
Contact description	4PDT
Features	Bifurcated contacts, Test button, With mechanical indicator
Terminal	Plug-in

## Fits to



### PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



### PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



### PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



### PYF14-ESS-B

Socket, with common, NC & NO terminals at the top and the coil terminals at the bottom - Black



### PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



### PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### Industrial Relays Brochure

EN PDF 2.77 MB



### MY(S) Miniature Power Relays Datasheet

EN PDF 9.29 MB



### OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB



### Solution case study No.8 Environment resistance

Brochure

EN PDF 623 KB