



MYQ4Z 200/220VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, , bifurcated contacts

Specifications

Mounting method	With plug-in socket
Usage	General purpose
Poles	4
Rated carry current	1 A
Coil voltage	220 V
Operation voltage	AC
Contact material	Ag alloy + Au plating
Contact description	4PDT
Features	Au plating, Bifurcated contacts, Plastic sealed, Transparent case
Terminal	Plug-in

Fits to



PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



PYF14-ESS-B

Socket, with common, NC & NO terminals at the top and the coil terminals at the bottom - Black



PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 26 April, 2024. Click here for [terms of use](#).

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Industrial Relays Brochure

EN PDF 2.77 MB



MY(S) Miniature Power Relays Datasheet

EN PDF 9.29 MB



OMRON Manufacturing Know-How: High Quality Relays Leaflet

EN PDF 449 KB



Solution case study No.8 Environment resistance Brochure

EN PDF 623 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 26 April, 2024. Click here for [terms of use](#).