



NB3Q-TW00B

Touch screen HMI, 3.5 inch QVGA (320 x 240 pixel), TFT color

Specifications

Screen diagonal	3.5 in
Number of pixels, horizontal	320
Number of pixels, vertical	240
Type of display	TFT
Frame colour	Black
Number of Ethernet ports	0
Number of USB ports	2
Number of RS-232 ports	1
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colours of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	129.8 mm
Height of the front	103.8 mm
Width of panel cutout	119 mm
Height of panel cutout	93 mm
Built-in depth	52.8 mm
Product Weight (unpacked)	480 g

Accessories



CP1W-CN221

USB Programming cable, A-type male to B-type male, 1.8 m



NB3Q-KBA04

Accessory HMI, protective sheets for NB3Q (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

Downloads

CAD Library



Maxell CR-series button cells
Battery Safety Datasheet

EN PDF 132 KB



NB Faceplate 3.1 - Multilanguage
Software

EN ZIP 75.3 MB



NB Series HMI
Datasheet

EN PDF 5.26 MB



NB Series Programmable Terminal
Brochure

EN PDF 3.26 MB



NB-Designer Setup v1.5.3.1
Software

EN ZIP 374 MB



NB-Series
Getting Started Guide

EN PDF 10 MB



NB-Series
Setup Manual

EN PDF 6.08 MB



NB-Series Host Connection
Setup Manual

EN PDF 21.3 MB



NB-series Programmable Terminals (Europe)
Discontinuation Notice

EN PDF 127 KB

