



NB7W-TW01B

Touch screen HMI, 7 inch WVGA (800 x 480 pixel), TFT color, Ethernet + USB Host

Specifications

Screen diagonal	7 in
Number of pixels, horizontal	800
Number of pixels, vertical	480
Type of display	TFT
Frame colour	Black
Number of Ethernet ports	1
Number of USB ports	2
Number of RS-232 ports	2
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colours of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	202.0 mm
Height of the front	148 mm
Width of panel cutout	191 mm
Height of panel cutout	137 mm
Built-in depth	46 mm
Product Weight (unpacked)	1000 g



CP1W-CN221

USB Programming cable, A-type male to B-type male, 1.8 m



NB7W-KBA04

Protective sheets for NB7W (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

CAD Library



EVE CR-series button cells Battery Safety Datasheet

EN PDF 380 KB



How to Import PLC Variables from Sysmac Studio Practice Guide

EN PDF 534 KB



NB Faceplate 3.1 - Multilanguage Software

EN ZIP 75.3 MB



NB Series HMI Datasheet

EN PDF 5.26 MB



NB Series Programmable Terminal Brochure

EN PDF 3.26 MB



NB-Designer Setup v1.5.3.1 Software

EN ZIP 374 MB



NB-Series Getting Started Guide

EN PDF 10 MB



NB-Series Setup Manual

EN PDF 6.08 MB



NB-Series Host Connection Setup Manual

EN PDF 21.3 MB



NB-series Programmable Terminals (Europe) Discontinuation Notice

EN PDF 127 KB



NB7W-TW1_B HMIs Users Manual

EN PDF 43.4 MB