



## NX-ID3444

4 Digital Inputs, High speed Timestamp, PNP 24 VDC, screwless push-in connector, 12 mm wide

# Specifications

I/O system	NX I/O Bus
Type of module	Digital I/O
Number of digital inputs	4
Digital input type	PNP
Permitted voltage at input	15-28.8 V
OFF/ON delay	0-0.0001 ms
Number of digital outputs	0
Digital output type	None
Short-circuit protected outputs	✘
Connection method	2-wire, 3-wire
Signal processing	High speed, Timestamp
IO-Link master	✘
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✔
Suitable for safety functions	✘
SIL according to IEC 61508	None
Communication port(s)	None
Number of IOV (V+) terminals	4
Number of IOG (V-) terminals	4
Number of COM terminals	0
Degree of protection (IP)	IP20
Product Height (unpacked)	104.5 mm

Product Width (unpacked)	12 mm
Product Depth (unpacked)	80.1 mm
Product Weight (unpacked)	65 g

## Accessories



**NX-AUX02**

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)

## Spare parts



**NX-TBA122**

Replacement screwless push-in connector with 12 wiring terminals (marked A+B)

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### IO-Link Series Brochure

EN PDF 7.5 MB



### Machine Safety Solution Brochure

EN PDF 2.86 MB



### NX-HAD Brochure

EN PDF 1.22 MB



### NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.84 MB



### NX-series Reference Manual

EN PDF 1.09 MB



### NX-series Digital I/O Unit - NX-ID/IA/OD/OC/MD Datasheet

EN PDF 4.49 MB



### NX-series Digital I/O Units Users Manual

EN PDF 10.1 MB



### Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



### PLC I/O Interface Wiring System Selection Connection Guide

EN PDF 1.56 MB



### Sysmac Catalogue

EN PDF 43.5 MB



### Sysmac: A Fully Integrated Platform Brochure

EN PDF 11.8 MB