



NX-OC2633

2 Digital Outputs, Normally-open Relays, 2 A, 250 VAC, screwless push-in connector, 12 mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Digital I/O
Number of digital inputs	0
Digital input type	None
OFF/ON delay	0-15 ms
Number of digital outputs	2
Digital output type	Relay NO
Permitted voltage at output	0-250 V
Output current	2 A
Short-circuit protected outputs	✘
Connection method	2-wire
Signal processing	Free running, Standard speed
IO-Link master	✘
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✔
Suitable for safety functions	✘
SIL according to IEC 61508	None
Communication port(s)	None
Number of IOV (V+) terminals	0
Number of IOG (V-) terminals	0
Number of COM terminals	0
Degree of protection (IP)	IP20

Product Height (unpacked)	100 mm
Product Width (unpacked)	12 mm
Product Depth (unpacked)	80 mm
Product Weight (unpacked)	65 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)

Spare parts



NX-TBA082

Replacement screwless push-in connector with 8 wiring terminals (marked A+B)

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 7.5 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX-HAD Brochure

EN PDF 1.22 MB



NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.84 MB



NX-series Digital I/O Unit - NX-ID/IA/OD/OC/MD Datasheet

EN PDF 4.49 MB



NX-series Digital I/O Units Users Manual

EN PDF 10.1 MB



Omron GX-JC0x-x EtherCAT Junction Box EtherCAT ESI file

EN ZIP 3.36 KB



Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



PLC I/O Interface Wiring System Selection Connection Guide

EN PDF 1.56 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 11.8 MB