



NX-OD3268

4 Digital Outputs, Standard speed, PNP 24 VDC, 2 A/point, 8 A/NX unit, screwless push-in connector, 12 mm wide

Specifications

| | |
|---------------------------------|---|
| I/O system | NX I/O Bus |
| Type of module | Digital I/O |
| Number of digital inputs | 0 |
| Digital input type | None |
| Number of digital outputs | 4 |
| Digital output type | PNP |
| Permitted voltage at output | 15.0-28.8 V |
| Output current | 2 A |
| Short-circuit protected outputs | ✓ |
| Connection method | 2-wire, 3-wire |
| Signal processing | Free running, Standard speed, Synchronous |
| IO-Link master | ✗ |
| I/O connection type | Push-in |
| Number of I/O connectors | 1 |
| Detachable I/O connector | ✓ |
| Suitable for safety functions | ✗ |
| SIL according to IEC 61508 | None |
| Communication port(s) | None |
| Number of IOV (V+) terminals | 6 |
| Number of IOG (V-) terminals | 6 |
| Number of COM terminals | 0 |
| Degree of protection (IP) | IP20 |
| Product Height (unpacked) | 106 mm |

Product Width (unpacked) 12 mm

Product Depth (unpacked) 80 mm

Product Weight (unpacked) 70 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)

Spare parts



NX-TBA122

Replacement screwless push-in connector with 12 wiring terminals (marked A+B)

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 7.5 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX-HAD Brochure

EN PDF 1.22 MB



NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.84 MB



NX-series Reference Manual

EN PDF 1.09 MB



NX-series Digital I/O Unit - NX-ID/IA/OD/OC/MD Datasheet

EN PDF 4.49 MB



NX-series Digital I/O Units Users Manual

EN PDF 10.1 MB



Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



PLC I/O Interface Wiring System Selection Connection Guide

EN PDF 1.56 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 11.8 MB